

Active Subwoofer **GTb 8200 A**

8"/200mm | 200 watts Max.Power | Class-D Amplifier



Sales Start
January 2014

Order number
1 061 343 495 001

EAN Code
4260 275 271 208

Highlights

- Bassreflex Subwoofer enclosure with integrated Class-D Amplifier
- Small dimensions: 250 x 272 x 260 mm
- 200mm/8" Subwoofer with Spun Paper Cone (SPC)
- Amplifier with high power handling: 75 watts RMS / 200 watts Max.Power
- Perfect matching Subwoofer
- Signal input via RCA/Cinch and highlevel
- Separate controls for lowpass filter, phase and gain
- Automatic On-/Off function via highlevel, RCA/Cinch and remote signal
- Central positioned Subwoofer
- Metall speaker protectors
- MDF housing material
- Stitched Blaupunkt logo on the top
- Perfect Price/Performance ratio

DISTRIBUTED BY:

BLAUPUNKT EUROPE GMBH, ROBERT-BOSCH-STRASSE 200, 31139 HILDESHEIM | SALES-BPE@BLAUPUNKT.COM

Active Subwoofer **GTb 8200 A**

8"/200mm | 200 watts Max.Power | Class-D Amplifier

Technical Data

Amplifier

• Technical concept:	Class-D
• Max. Power (watts):	200
• RMS Power (watts):	75
• Frequency response (Hz):	30–200
• Lowpass filter (Hz):	70–190
• Phase (°):	0 - 180
• Gain (V):	0.3 – 8
• Inputs Cinch (RCA) /Highlevel:	2 / 2
• Automatic On-/Off function:	after 30 Sek.
• Power-On indicator color:	green
• Protection indicator color:	red
• Integrated fuse (number/size):	1 / 7,5A



Subwoofer

• System:	Single Cone Subwoofer
• Diameter (mm/inch):	200/8"
• Impedance (ohms):	2x2
• Frequency range (Hz):	30-200
• SPL dB(2.83 V/m):	92
• Membrane material:	Spun Paper Cone (SPC)

Housing

• System:	Bassreflex
• Surface material/color:	carpet / black
• Connectors 12V/Ground/Remote signal:	Screw terminals
• Dimensions (W x H x D):	250 x 260 x 270/202 mm 10.0 x 10.2 x 10.7/8.0"
• Weight:	6,9 Kg

Accessories included in delivery

• Installation and user manual:	yes
• Metal protectors for the Subwoofer:	yes

