

Kamasa-TOOLS®

Fuel Filter
Removal
Kit

K 10675



INTRODUCTION

The diesel fuel filter removal kit has been developed to assist the removal and replacement of the filter element without risk of damaging the filter plastic body.

These filter housings are not disposable and the filter is supplied as an element only.

The two piece kit provides a vice stand for the filter outer body to be held securely and an adaptor which fits snugly onto the top of the filter housing to allow a 1/2"D wrench to be used to separate the top of the filter housing from the body.

Applications: Chevrolet, Citroën, Fiat, Saab, Suzuki, Vauxhall/Opel

Engines: 1.3 JTD / CDTi / DDiS, 1.9 JTD / CDTi / TiD, 2.0 VCDi / HDi / JTD, 2.2 JTD / HDi, 2.8 JTD / HDi, 3.0 JTD / HDi



Removal Adaptor

Filter Body Stand

INSTRUCTIONS

- Remove the filter body completely from the vehicle
- Mount the filter housing body as shown in the filter body stand and place in a suitable vice, do not over tighten the vice.
- Place the removal adaptor on the top of the filter housing and loosen.
- Remove the internal filter element, clean the internals of the filter housing and insert new filter.
- Fit new filter housing seal and ensure correct alignment then tighten filter housing to recommended torque.





Kamasa Tools is a registered trademark of
KG Knutsson AB, 191 81 Sollentuna, Sweden

K 10675

www.kamasatools.com