

Product information

Meguin Mehrzweckfett L2



Description

Multi-purpose grease based on a lithium soap.

Properties

Resistant to aging, with good corrosion and wear protection properties.

Approvals and recommendations

Lincoln lubrication systems

Application

Particularly suitable for the lubrication of normally stressed roller and plain bearings which operate at normal to high rotational speeds, also used under dusty and damp conditions. Its long shelf life and operating time guarantee economical use in a wide range of applications.

Temperature range

-25 °C to +120 °C
short periods up to +130 °C

Characteristic data

Brief description	K2K-20 DIN 51502
NLGI number	2 DIN 51818
Saponification type	Lithiumseife
Worked penetration	265-295 1/10 mm DIN ISO 2137
Dropping point	185 °C DIN ISO 2176
Oil separation after 18 hours at 40 °C	2,2 % DIN 51817
Oil separation after 7 days at 40 °C	5,8 % DIN 51817
Flow pressure at -20 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1 Mineralöl
Viscosity at 40 °C	100,0 mm ² /s ASTM D 7042-04
Flash point	240 °C DIN ISO 2592



Characteristic data

Pour point	-24 °C DIN ISO 3016
------------	------------------------

Application

Particularly suitable for the lubrication of normally stressed roller and plain bearings which operate at normal to high rotational speeds, also used under dusty and damp conditions. Its long shelf life and operating time guarantee economical use in a wide range of applications.

Available pack sizes

400 g Cartridge plastic	4770 D-GB-F-HR-RUS-GR
400 g Lube-Shuttle	9028 D-GB-F-HR-RUS-GR
1 kg Can sheet metal	4774 D-GB
5 kg Bucket plastic	4771 D-GB
15 kg Bucket plastic	6482 D-GB
25 kg Bucket plastic	4773 D-GB
50 kg Bucket black plate	4775 D-GB
180 kg Black plate barrel	4863 D-GB