


## SPECIFICATION CONTROL DRAWING



Product Revision		Size Code Color Items 3	Product Dimensions		Conductor Dimensions		Selection Guide			
Product Name	L max		øA min	øB		Total mm <sup>2</sup>		Total CMA		
				min	max	min	max	min	max	
CWT-9001	C	Clear	26.0 (1.025)	1.7 (0.065)	0.4 (0.015)	1.7 (0.065)	0.3	0.8	450	1500
CWT-9002	B	Red	42.0 (1.655)	2.7 (0.105)	1.3 (0.050)	2.7 (0.105)	0.8	2.0	1250	3500
CWT-9003	B	Blue	42.0 (1.655)	4.5 (0.180)	1.8 (0.070)	4.5 (0.180)	2.0	4.0	2500	7200
CWT-9004	B	Yellow	42.0 (1.655)	6.0 (0.235)	2.8 (0.110)	6.0 (0.235)	4.0	6.0	6100	19000
CWT-9005	B	Grey	42.0 (1.655)	7.0 (0.275)	3.2 (0.125)	7.0 (0.275)	6.0	10.0	12000	25000

### MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, radiation cross-linked modified polyolefin. Transparent clear.
2. SOLDER PREFORM WITH FLUX:  
SOLDER: TYPE CD18 per ANSI/J-STD-006.  
FLUX: TYPE ROM1 per ANSI/J-STD-004.
3. MELTABLE RINGS: Thermally stabilized thermoplastic. Color: see table.

### APPLICATION

1. These controlled soldering devices are designed to splice tin-plated or bare copper stranded wires rated for at least +85°C.
2. Temperature range: -55°C to +125°C.
3. For installation procedure and application equipment consult RPIP-824-00.

For best results, prepare the wires as shown:

