MAX COMFORT. MAX CONTROL. MAX SAFETY.



Maintain your original ride-height even when fully laden & remain safe and comfortable as well unladen With MAD auxiliary coil suspension for your Volkswagen Transporter T5-T6



Why auxiliary coil suspension

- Better road holding and handling when laden
- Constant towball height
- More suspension travel with full load
- Improved driver comfort



Auxiliary springs HV-198075

2300 2300 1900 1800 1700 1800 1200 1400 1500 1400 1500 530 520 510 500 450 439 470 460 450 440 430 420 410 400 390 380 370 380 height (m.m)

Auxiliary suspension characteristic

Benefits of MAD auxiliary coil suspension

- Lifetime warranty on material
- No drilling or welding
- MAD Suspension maintain the original ride height
- MAD Suspension are quickly and easily installed
- Does not affect vehicle warranty
- TüV approved
- Fast delivery due to large stock volumes

MAD part numbers

--- original

HV-198075 Auxiliary

HV-198135 Kit for Car with GPL/CNG

HV-198218 Reinforced Mainsprings

HV-198238 Medium Duty, Minimum Load 300 kg
HV-198158P Heavy Duty, Minimum Load 500 kg

MAX COMFORT. MAX CONTROL. MAX SAFETY.



MAD Lift Springs

even when fully laden & remain safe and comfortable as well unladen With MAD Lift Springs for Volkswagen Transporter T5-T6.


Benefits:

More Groundclearance - prevent bottoming Enhanced Roadholding on rough roads Progressive Springs Without replacing the original shockabsorbers





Reinforced Front Springs



Spring characteristic Front Springs

Benefits of MAD reinforced coil suspension

- Lifetime warranty on material
- No drilling or welding
- MAD Suspension are quickly and easily installed
- Does not affect vehicle warranty
- TüV approved
- Fast delivery due to large stock volumes

MAD part numbers

HV-198081 with Auxiliary spring on the rear axle + 30 mm

HV-198201P with reinforced replacement springs for rear axle + 30 mm

HV-198271 Medium Duty, minimum load 300 kg **HV-198171P** Heavy Duty, minimum load 500 kg

All above kits are with progressive Reinforced Coilsprings for Front Axle +30 mm