

## Viscous Grease ZS KOOK-40

### Description

Lithium soap grease, made from carefully selected raw materials and additives. Its ideal lubricity, water resistance, adhesiveness and high-pressure resistance makes it stand out. Designation acc DIN 51502 K00 K-40.

### Properties

- excellent adhesion
- good water resistance
- minimizes wear
- outstanding lubricating action

### Technical data

Brief description	K00/000K-40 DIN 51502
NLGI number	00/000 DIN 51818
Worked penetration	400-460 1/10 mm DIN ISO 2137
Dropping point	165 °C DIN ISO 2176
Flow pressure at -40 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1
Base oil	
Viscosity at 40 °C	45 mm <sup>2</sup> /s ASTM D 7042-04
Flash point	184 °C DIN ISO 2592
Pour point	-36 °C DIN ISO 3016

### Areas of application

Especially suited for truck central lubrication systems. As normal in viscous greases, comply with the transmission and bearing manufacturers' operating instructions.

### Application

Use as usual for flow greases. The operating instructions of the transmission and bearing manufacturers must be followed.



### Available pack sizes

5 kg Bucket plastic	4714 D-GB
25 kg Bucket plastic	4715 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**