

JACOBS 500 / 5000 SERIES®

Application

- 500 Series—Recommended for professional grade DC Rotary Drills
- 5000 Series—Recommended for professional grade AC Rotary Drills



Features & Benefits

- Serrated jaw bite increases grip up to 300% over standard bite chucks.
- Jacobs patented Hammerlock® technology provides a positive locking mechanism which prevents loosening in hammer and other high vibration applications.
- Jacobs patented Anti-Lock prevents chuck from locking open.
- Single sleeve versions for drills with spindle locks to provide a larger gripping surface and one-handed tightening.
- Patented Torx® Technology for easy mounting.

Jacobs[®]
C H U C K

JACOBS 500 / 5000 SERIES®

Specifications

Model Number	Description	Capacity			Drill Rating	Hard Pin Grip Torque		Runout		Drill Type	
		inches	mm	Mount		Ft-lb In/Ft-lb Out	Nm In/Nm Out	inches	mm	Rotary	Spindle Lock
510-2P	Two Sleeve Plastic	3/8	10mm	3/8" x 24	12-18 volts DC Drills	6.67/6.67	9.04/9.04	0.014	0.36	Y	N
510-1P	One Sleeve Plastic	3/8	10mm	3/8" x 24	12-18 volts DC Drills	6.67/6.67	9.04/9.04	0.014	0.36	Y	Y
510-2H	Plastic Front, Metal Rear	3/8	10mm	3/8" x 24	12-18 volts DC Drills	6.67/6.67	9.04/9.04	0.014	0.36	Y	N
513-2P	Two Sleeve Plastic	1/2	13mm	1/2" x 20	12-24 volts DC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	N
513-1P	One Sleeve Plastic	1/2	13mm	1/2" x 20	12-24 volts DC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	Y
513-2H	Plastic Front, Metal Rear	1/2	13mm	1/2" x 20	12-24 volts DC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	N
513-1M	One Sleeve Metal	1/2	13mm	1/2" x 20	12-24 volts DC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	Y
513-2M	Two Sleeve Metal	1/2	13mm	1/2" x 20	12-24 volts DC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	N
5013-1M	One Sleeve Metal	1/2	13mm	1/2" x 20	Up to 8.5 amps/1050 watts AC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	Y
5013-2M	Two Sleeve Metal	1/2	13mm	1/2" x 20	Up to 8.5 amps/1050 watts AC Drills	8.33/11.08	11.30/15.03	0.014	0.36	Y	N



**510
2 SLEEVE
PLASTIC FRONT/METAL REAR**

**JACOBS
NORTH AMERICA**
World Headquarters
and U.S. Factory
One Jacobs Road
P.O. Box 592
Clemson, SC 29633, USA
Phone: 864.654.5926
Fax: 864.654.5001



**513/5013
1 SLEEVE
METAL**

**JACOBS
EUROPE**
Distribution Center
The Jacobs Manufacturing Co.
Danaher House
Parkway One Business Centre
Parkway Drive
Sheffield
South Yorkshire, S9 4WU
England
Phone: 011 44 114 256 4200
Fax: 011 44 114 256 4201



**513/5013
2 SLEEVE
METAL**

**JACOBS
ASIA**
Manufacturing & Sales
No 26
Baiyu Road
Suzhou Industrial Park
Suzhou, Jiangsu Province, China
215021
Phone: 011 86 512 6761 6165
Fax: 011 86 512 6761 2066

www.jacobschuck.com

©2006 The Jacobs Chuck Manufacturing Co. 500 Series®, Hammerlock® and Jacobs® are registered trademarks of The Jacobs Chuck Manufacturing Co. Torx® is a registered trademark of Camcar, a division of Textron, Rockford, IL.

JACOBS
CHUCK