

**You'll never run
out of air again.**

The ContiMobilityKit
for extended movability.

- › Easy to use repair kit for sealing and re-inflating a punctured tyre
- › Ensuring an unaltered driving performance for another 200 km at a maximum 80 km/h
- › Original equipment quality
"Engineered in Germany"



The convenient solution to go.

The ContiMobilityKit is a comfortable repair kit, designed to seal punctures in the tyre tread caused by nails or similar objects with a diameter of up to 6 mm. The kit consists of a compact compressor and a separate sealant bottle, with a shelf life of up to 5 years. In case of a puncture, an emergency roadside tyre change is not necessary and the journey can be continued for another 200 km at a maximum speed of 80 km/h. It's not even required to remove and replace the valve core, with only a few steps you are ready to go again. The ContiMobilityKit is only suited for passenger car tyres with a mandatory tyre pressure of maximum 3 bar.

Product contents:

- › Compressor
- › Pressure-resistant tyre sealant bottle
- › User manual
- › Bag
- › Gloves

Technical specifications of compressor:

Amperage	Voltage	Maximum pressure
Max. 10 A according to DIN ISO 8820	12 V	700 kPa (7 bar, 102 psi)
Dimensions	Weight	Area of application
150 mm x 130 mm x 60 mm	650 g	-30° C to +60° C

Technical specifications of sealant bottle:

Sealant amount	Shelf life	Dimensions
450 ml	5 years	Ø 87 mm x 125 mm
Weight	Application temperature	
585 g	-30° C to +60° C	

Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi).

Tyre width in mm	Tyre cross section											Rim size in inches		
130 195	25 - 80											R 10 R 14		
135/	25	30	35	40	45	50	55	60	65	70	75	80	R 15	
145/	25	30	35	40	45	50	55	60	65	70	75	80		
155/	25	30	35	40	45	50	55	60	65	70	75	80		
165/	25	30	35	40	45	50	55	60	65	70	75	80		
175/	25	30	35	40	45	50	55	60	65	70	75	80		
185/	25	30	35	40	45	50	55	60	65	70	75	80		
195/	25	30	35	40	45	50	55	60	65	70	75	80		
205/	25	30	35	40	45	50	55	60	65	70	75			
215/	25	30	35	40	45	50	55	60	65	70				
225/	25	30	35	40	45	50	55	60	65					
235/	25	30	35	40	45	50	55	60						
245/	25	30	35	40	45	50	55							
155/	25	30	35	40	45	50	55	60	65	70	75	80	R 16	
165/	25	30	35	40	45	50	55	60	65	70	75	80		
175/	25	30	35	40	45	50	55	60	65	70	75	80		
185/	25	30	35	40	45	50	55	60	65	70	75	80		
195/	25	30	35	40	45	50	55	60	65	70	75	80		
205/	25	30	35	40	45	50	55	60	65	70				
215/	25	30	35	40	45	50	55	60	65					
225/	25	30	35	40	45	50	55	60						
235/	25	30	35	40	45	50	55							
245/	25	30	35	40	45	50								
185/	25	30	35	40	45	50	55	60	65	70	75			R 17
195/	25	30	35	40	45	50	55	60	65	70				
205/	25	30	35	40	45	50	55	60	65					
215/	25	30	35	40	45	50	55	60	65					
225/	25	30	35	40	45	50	55	60						
235/	25	30	35	40	45	50	55							
245/	25	30	35	40	45	50								
255/	25	30	35	40	45									
265/	25	30	35	40										
275/	25	30	35											
285/	25	30	35											
205/	25	30	35	40	45	50	55	60					R 18	
215/	25	30	35	40	45	50	55	60						
225/	25	30	35	40	45	50	55	60						
235/	25	30	35	40	45	50								
245/	25	30	35	40	45									
255/	25	30	35	40	45									
265/	25	30	35	40										
275/	25	30	35											
285/	25	30	35											
295/	25	30												
215/	25	30	35	40	45	50	55							R 19
225/	25	30	35	40	45	50	55							
235/	25	30	35	40	45	50								
245/	25	30	35	40	45									
255/	25	30	35	40										
265/	25	30	35											
275/	25	30	35											
225/	25	30	35	40	45								R 20	
235/	25	30	35	40	45									
245/	25	30	35	40										
255/	25	30	35											
265/	25	30	35											
275/	25	30	35											