

Vavigation Lights



Signalling Lights





Whistles


DHR**150** & **180** LED





DHR decided to develop a drop-in LED replacement for both the **150**- as the **180**-series. No special modifications are needed for installation. Simply plug-and-play and enjoy a hassle-free usage of this searchlight for a lifetime.

KEY PERFORMANCE INDICATORS





PERFORMANCE & FEATURES

Model	150-series	180-series		
Electrical	<u>'</u>	'		
Voltage	10 - 32VDC	10 - 32VDC		
Power consumption	10W	20W		
Preferred cable type	H07RN-F	H07RN-F		
Cable diameter	Ø 6-9 mm	Ø 6-9 mm		
Optics				
Lamp size equivalent	PAR46	PAR56		
Type optic	Polycarbonate	Polycarbonate		
	mirror reflector	mirror reflector		
Range	447 m	612 m		
Beam Angle	3° x 2,5°	3° x 2,5°		
Luminous intensity	200.000	375.000		
Average life-time	50.000 h	50.000 h		
Environmental				
Operating temperature	- 40° / +	- 40° / + 55° C		
Ingress protection class	IP56			
Housing				
Material	AW6082 Aluminium +	AW6082 Aluminium + 316L Stainless steel		
Finish	Black anodized, stainless steel ring			

Available Models				
Туре	DS	СВ	CS	UC

150-series

Front glass

Seals





Borosilicate Toughened Glass

Silicone / Neoprene, black

180-series











Fascinatio Boulevard 1182 2909 VA Capelle a/d IJssel The Netherlands T +31 (0) 10 413 07 55

E sales@dhr.nl www.dhr.nl

